

SPECIFICATION SHEET

Glove Style: NITRIchem

Description:

Flock lined Nitrile formula resistant to solvents & oil based chemicals curved figure design and contoured palm helps reduce hand fatigue multiple size selection with raised grip pattern on palm

Series:

NITRIchem

Sizes Available:

SIZE AS PER EN 420	MARKED SIZE
8 9 10 11	
*Indicates fit for special purpose Glove measured when laid flat and relaxed	

Cleaning & Maintenance:

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed however, should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand & remove the gloves without the contaminant contacting the bare hands. The gloves may then be de-contaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement. All gloves should be thoroughly inspected before use to ensure no damage is present.

Storage:

Store the gloves the original packaging in a cool dry place and out of direct sunlight.

Packaging:

The standard packaging for the gloves are as follows. The gloves are not packed in individual bags "inbg". The gloves are packed in bundles in a polybag "plbg". The "plbg" glove bundles are placed in cardboard cartons "ctn" suitable for transportation and storage.

Obsolescence:

Stored correctly, the gloves physical properties will not change for up to three years.

General:

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer. The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection. The gloves are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment so it is therefore the responsibility of the end user and not the manufacturer or supplier to determine the gloves suitability for the intended use.

NITRIchem

GREEN NITRILE GLOVE



INTERMEDIATE
DESIGN

MARKING



NITRI chem



Tested in accordance with the European directive for PPE (89/686/EEC) for intermediate design, and is tested to EN 388.



BOA SAFETY SOLUTIONS (PTY.) LTD.
www.boasafety.co.za



NITRlchem



EN 388:1994
MECHANICAL RISKS



A B C D

A ABRASION RESISTANCE
Number of cycles (6.1)

1	2	3	4	5
100	500	2000	8000	~

B BLADE CUT RESISTANCE
Index (6.2)

1	2	3	4	5
1,2	2,5	5,0	10,0	20,0

C TEAR RESISTANCE
Newton's (6.3)

1	2	3	4	5
10	25	50	75	~

D PUNCTURE RESISTANCE
Newton's (6.4)

1	2	3	4	5
20	60	100	150	~

